

2.6.10


ORDINANCE TO AMEND CERTAIN PROVISIONS OF THE CITY OF URBANA PLUMBING CODE.

BE IT ORDAINED by the City Council of the City of Urbana, Illinois, that the plumbing ordinance be, and is hereby amended in regard to certain provisions as follows:


1. Revise Plumbing Ordinance to substitute the word licensed plumber for all references to Master and Journeyman Plumber and delete all reference to Plumber's Apprentice.
2. Add to plumbing ordinance under Article II Licensed Plumber. A Licensed Plumber within the writing of this ordinance is a person who has a license in effect from the Department of Registration and Education of the State of Illinois, specifying such person as a Licensed Plumber.
3. Revise plumbing ordinance Article V Section 2, Paragraph 1, reading as follows: " Before issuing such a permit, an application shall be filed by a Master Plumber with the Commissioner of Public works"; and the same shall be revised to read as follows: " Before issuing such a permit, an application shall be filed by a licensed plumber or a qualified drain-layer, as approved by the Commissioner of Public Works "
4. Revise Plumbing ordinance Article VIII, Section 2, to read as follows: "VITRIFIED PIPE. All joints in vitrified clay pipe shall be made by caulking a processed fibrous core tightly in place so that the spigot of each pipe shall be held firmly and concentrically in the bell. The core shall be completely impregnated with selected asphalts containing an inhibitor to prevent bacterial fungus growth. The saturant shall be very adhesive and shall have a low susceptibility to temperature changes. The joint shall be sealed with a cold-poured or a hot-poured asphaltic cement, hot-poured plastic type compound or it may be sealed with sealing compound applied cold with a trowel, but in all cases where such material is used the directions given by the manufacturer as to priming and method of application shall be carefully

followed. If a special material is required because of acids or other fluids corrosive and harmful to the pipe or usual joint materials, specifications must be prepared by a licensed Architect or Engineer and carefully followed by the owner or contractor. Factory-poured slip joints may be used and formed out of either asphalt or asphaltic compound or plastic material. Where solvents are needed before the placing of such pipe, or in any case where such pipe is used the requirements of the manufacturer shall be carefully followed. No foreign material shall be left within the pipe and before making final connection, a swab or scraper shall be dragged through the connection to remove all such foreign material."

Adopted by the City Council of the City of Urbana,
Illinois, this 19th day of January A. D. 1959.


CITY CLERK

Approved by the Mayor this 19th day of January A.D. 1959.


MAYOR.